

COLORFAST PIGMENT SYSTEM



DESCRIPTION:

- Environmentally-friendly colorants
- Meets SCAQMD Rule 1113 - VOC Less than (<) 50 g/l
- Broad color space potential
- Fade Resistant

USES:

- Low VOC colorant for use in the following Parex USA exterior finishes and coatings:
 - DPR Acrylic Finishes
 - Elastomeric Finishes
 - DPR Coatings
 - Elastomeric Coatings
 - Specialty Finishes
 - Primers
 - Color Bottles

COMPOSITION:

- Binder Base: 100% Acrylic
- Color: 11 Colorant System

PAREX USA COLORFAST PIGMENTS	
AX – Yellow	FX – Red Oxide
CX – Yellow Oxide	RX – Red
EX – Blue	LX – Raw Umber
DX – Green	MX – Magenta
IX – Brown Oxide	BX – Black
KX – White	

- Pigment: Water-based

PAREXUSA

PRODUCT DESCRIPTION	Canister Code	Typical LBS/GALLON	SPECIFIC GRAVITY	VISCOSITY (KU)	ACID RESISTANCE OF COLORANT	ALKALI RESISTANCE OF COLORANT	MAX HEAT FASTNESS OF COLORANT (°C for 30min exposure)
COLORFAST KX WHITE	KX	16.1	1.93	65-85	5	5	250
COLORFAST CX YELLOW OXIDE	CX	15.2	1.82	65-85	5	5	150
COLORFAST DX GREEN	DX	11.2	1.34	65-85	5	5	250
COLORFAST FX RED OXIDE	FX	17.1	2.05	65-85	5	5	150
COLORFAST BX BLACK	BX	11.3	1.36	65-85	5	5	250
COLORFAST LX RAW UMBER	LX	12.6	1.44	65-85	5	5	250
COLORFAST RX RED	RX	10.2	1.22	60-80	5	5	180
COLORFAST AX YELLOW	AX	13.2	1.58	60-80	5	5	150
COLORFAST EX BLUE	EX	11.2	1.34	60-80	5	5	180
COLORFAST IX BROWN OXIDE	IX	14.3	1.72	65-85	5	5	150
COLORFAST MX MAGENTA	MX	9.2	1.11	67-87	5	5	200

All colorants meet SCAQMD Rule 1113 VOC less than (<) 50 g/L
1=Poor, 5=Excellent

CONTAINER

- 1 Liter(1.056 qt)
- Storage: Protect from direct sunlight and freezing at all times
- Shelf Life: Reference Parex USA Expiration Date of Products Technical Bulletin.

MIXING

- Shake container three (3) minutes via hand or shaker.

APPLICATION

- Empty contents into tinting machine; completely empty container.
- Scrape sides to ensure all colorant is loaded into tint machine.

- Keep lid on container when not in use.
- Best practice is to fill the tint machine at the end of the day, to allow any entrained air from shaking to escape the product before use.

WARNING

- Read complete Warning information printed on product container prior to use. For medical emergency information, call 1-800-424-9300.
- For more information on handling this product refer to its Safety Data Sheet (SDS). The most current SDS and Product Data Sheet (PDS) can be found on our website.

- This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Parex USA, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

PAREXUSA

Parex USA, Inc., A California Corporation
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
www.parexusa.com
866-516-0061 Tech Support: 800-226-2424